

NZCA00065 Cabot's Deck Clean

Introduction

Part A
918 82195

Description and Image

Cabot's Deck Clean is an essential preparation product that cleans and rejuvenates new and old exterior timber surfaces prior to applying a top coat of oil, stain, paint or exterior varnishes. It is designed to revitalise and clean grey, weathered and soiled timber and removes naturally occurring tannins from new timber. It is also effective in removing mould and other contaminants.



Features and Benefits

- Removes tannin stains.
- Combats mould, dirt & grease.
- Easy to use.
- Prepares timber for recoat.
- Helps remove tannin and oils that leach from new timber.
- Effectively cleans mould, dirt, grease and other contaminants that are present.
- Water clean up and 15 minute rinse off.
- Prepares timber prior to coating for a longer lasting finish.



Uses

All bare, previously oiled or stained exterior timber including decking, steps and handrails, outdoor garden settings, BBQs, window frames, doors, weatherboards, pergolas etc.

Precautions and Limitations

Protect plants, bushes, metal and paint work that are not to be cleaned, with plastic sheets. Rinse off immediately and thoroughly if contact occurs.
Cabot's Deck Clean is not a paint remover, however it may remove some old and weathered coatings from timber.

Performance Guide	
Weather Not applicable	Salt Unaffected by splash or spillage
Heat Resistance Not applicable	Water Not applicable
Solvent Not applicable	Abrasion Not applicable
Acid Not applicable	Alkali Not applicable

Typical Properties	
Gloss Level N/A	Heat Thinner Water
Colour Blue	
Components 1	Number of Coats 1 or 2
Toxicity Poison. Contains oxalic acid	V.O.C. Level < 5g/L
Mixing Ratio 4:1	
Clean Up  Water	
Application Methods  Brush Broom	
Typical Property Notes Coverage One litre of Cabot's Deck Clean when diluted with four parts water will treat approx. 5-10 sq. metres.	

Application Guide

Surface Preparation

All timber

Note: Wear protective gloves and goggles when using this product.

Remove excessive dirt and oil contamination with hot soapy water using a stiff broom or brush. Hose area clean with water.

Precaution

Protect plants, bushes, metal and paint work that are not to be cleaned, with plastic sheets. Rinse off immediately and thoroughly if contact occurs.

Application Procedure and Equipment

Shake contents before use.

Test on a small area to determine effectiveness and strength required.

Add one part Cabot's Deck Clean to four parts water in a plastic bucket and mix well. For stubborn stains use a stronger solution.

Apply generously to the timber with a brush or broom. Scrub vigorously.

Leave the solution on the timber for 10-20 minutes. Rinse off the surface with water using a high pressure or garden hose. Avoid allowing to dry out.

Severely stained decks may need an additional treatment, more vigorous scrubbing or a power washer.

Hints

Cabot's Deck Clean is not a paint remover, however it may remove some old and weathered coatings from timber.

Health and Safety

SDS Number
3410

SDS Link
[View SDS Link](#)

Using Safety Precautions

Risk: Harmful in contact with skin and if swallowed. Irritating to eyes.

Contains: Less than 10% oxalic acid

Keep out of reach of children. Avoid skin and eye contact and breathing vapour. Provide adequate ventilation. If inhalation risk exists wear organic vapour respirator. Keep containers closed when not in use. If using inside keep windows and doors open during application and drying time.

For spills: Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. For disposal refer to information above.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Line Shade/Pack A
918 82195

Size:

Weight:

4 Litre 1 Litre

4.2 Kg 1.1 Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.co.nz. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.