

NZCA00095 Cabot's Danish Oil

Introduction

Part A
871-82113

Description and Image

CABOT'S Danish Oil is a penetrating oil for interior panelling to produce a soft lustre without obvious film build.

Features and Benefits

- Low sheen
- Polyurethane resin
- Clear finish
- Free flowing
- Gives "hand-rubbed" appearance
- Develops moderate hardness
- Enhances grain and colour
- Apply with brush or cloth

Uses

Use CABOT'S Danish Oil on interior timber panelling, trim, furniture and cupboards.

Precautions and Limitations

Do not apply product if temperature is below 10C or is likely to fall below 10C during the drying period.
Moisture content of timber should be close to equilibrium moisture content, usually 10-15%, but not exceeding 15%, for satisfactory application.
For interior use only.

Performance Guide

Weather For interior use only, not recommended for exterior use.	Salt Unaffected by splash or spillage
Heat Resistance Up to 120C. Premature yellowing and embrittlement will occur if subjected to continuous heat.	Water Good water resistance.
Solvent Resists mineral turpentine and similar solvents.	Abrasion Moderate resistance to abrasion.
Alkali N/A	

Typical Properties

Heat Thinner
Not required

Colour
Clear

Components
1

Number of Coats
2

Toxicity
Lead free. Dry film is non-toxic.

V.O.C. Level
590 g/L

Sanding Properties
Very good

Touch Dry
3 Hours

Clean Up



Thinner

Clean Up Description
Thoroughly clean all equipment with mineral turpentine

Application Methods



Brush



Roller



Pad

Application Conditions

Solids by Volume

28

Min

Max

Recommended

Wet Film Per Coat (microns)

100

Dry Film Per Coat (microns)

28

Recoat Time (min/hours)

8 Hours

Indefinite

Theoretical Spread Rate (m²/L)

10

Application Guide

Surface Preparation

All timber surfaces should be thoroughly clean, dry and free from wax, oil, grease and other contaminants. Wash with mineral turpentine if needed to remove wax and grease, allow to dry, and lightly sand dressed surfaces with "00" paper or finer, always in direction of the grain. For interior surfaces, fill nail holes with CABOT'S Wood Tone Putty - do not use a linseed oil putty.

Application Procedure and Equipment

Brush, short-nap roller or pad
Stir contents thoroughly before and during use with a broad flat stirrer, to maintain a uniform colour and solution.
Apply full even coat liberally to timber. Allow approx 10 minutes to penetrate and "set".
Wipe off excess with a soft lint free cloth, and finish wiping in direction of grain.
For greater lustre apply a second coat of Danish Oil after allowing 8 hours drying. Sand very lightly between coats. Finish can be buffed using a pad or folded cloth.
Alternatively, lightly sand while wet using 5/600 grit wet and dry paper, then buff.

Health and Safety

SDS Number
14184501

SDS Link
[View SDS Link](#)

Using Safety Precautions

For detailed information refer to the product label and the current Material Safety Data Sheet available through CABOT'S Sales and Customer Service Offices.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Line Shade/Pack A
871-82113

Size:

Weight:

4 Litre 1 Litre 500ml 250ml

3.8 Kg 1.0 Kg 500g 300g

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.co.nz. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.