

## NZPP00049 Porter's Paints Black Antique Wax

### Introduction

Part A  
PZ5-P1203

### Description and Image

**Porter's Black Antique Wax** is a fine black polish containing beeswax, elm gum turpentine and linseed oil. Designed to protect and age most bare or painted surfaces. Black Antique Wax is designed to create an aged effect by discolouring surfaces and laying on darker in crevices, cracks and low relief areas. Buff to desired lustre.

### Features and Benefits

- Polishes to a soft lustre. Can be re-applied as required.
- Pleasant smell.
- A natural finish using Australian bee's wax.
- Creates antique effects.

### Uses

Can be applied as a protective finish over bare timber or painted surfaces.  
Interior use for polishing furniture, shelving, mantle pieces and other timber household objects where an antiqued or aged wax finish is required.

✓ **Interior**

### Precautions and Limitations

Interior only.  
Not suitable for use in wet areas. Do not apply in high humidity, below 10°C or above 30°C.

Typical Properties			
Colour <b>Black</b>			
Components <b>1</b>		Number of Coats <b>1</b>	
Clean Up  Pure gum turpentine.			
Application Methods  Apply sparingly with a soft lint free cloth or fine steel wool.			
Application Conditions			
	Min	Max	Recommended
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="10"/>	<input type="text" value="12"/>	<input type="text" value="11"/>
Typical Property Notes Covers approximately 10-12m <sup>2</sup> per kg, depending upon porosity, surface texture and wastage rates.			

Application Guide
Surface Preparation Follow drying time instructions from the specification of the product you are coating.
Application Procedure and Equipment Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point. Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period.  Apply sparingly with a soft lint free cloth or fine steel wool. Ensure Black Antique Wax is sparingly and evenly applied. Before the wax is completely dry buff vigorously by hand with a soft clean cloth, or mechanically with a lamb's wool buffer.

Health and Safety	
SDS Number <b>DLXNZ7EN001304</b>	SDS Link <a href="#">View SDS Link</a>
Using Safety Precautions Keep out of reach of children. Read the label before opening or using. Use only outdoors or in a well ventilated area. Do not eat, drink or smoke when using this product.	
<b>Please refer to SDS Link. In case of emergency, please call 0800 220 770.</b>	

Transport and Storage	
Pack A <b>PZ5-P1203</b>	
Size: <b>Small can, Large can</b>	Weight: <b>225g, 3.7Kg</b>
Flash Point <b>32</b>	UN Number <b>1299</b>
Dangerous Goods Class <b>3</b>	Package Group <b>III</b>

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.