

## NZDU00408 Dulux Wash & Wear 101 +Plus Kitchen & Bathroom Low Sheen

### Introduction

Product Code  
**52A04912**

Approvals  
**Eco Choice Aotearoa License**

### Description and Image


Wash&Wear +PLUS Kitchen & Bathroom has been developed to withstand humid or damp environments. The hard wearing surface formed by Wash&Wear's exclusive Barrier Technology is fortified with a powerful mould inhibitor and water repellent properties. This gives lasting protection to rooms with damp or humid conditions such as kitchens, bathrooms and laundries. Wash&Wear +Plus Kitchen & Bathroom contains Barrier Technology so you can wipe away most marks with a wet cloth, meaning your walls will look freshly painted for years.



### Features and Benefits

- Water Based
- Ideal for rooms with high humidity or condensation
- Withstands frequent cleaning
- Low VOC & low odour
- Contains Mouldshield® Technology
- Easy application & quick drying
- Use in kitchens, bathrooms, and laundries.
- Keeps your walls looking freshly painted for years.
- Almost no paint smells
- Inhibits mould and bacterial growth on the painted surface

**Standards And Certifications**



Eco Choice Aotearoa  
Licensed Product

**Standards and Certifications**

For details on these standards and certifications please reference the 'Approvals' section at the beginning of this document. Please contact your DuluxGroup representative for specific information on ESD credits / points.

**Uses**

DULUX Wash&Wear +PLUS Kitchen & Bathroom Low Sheen is ideal for all walls and ceilings in humid or damp rooms.  
The Dulux 10 Year Guarantee: Dulux Wash&Wear +Plus Kitchen & Bathroom is guaranteed for 10 years against mould growth as long as Dulux Wash&Wear +Plus Kitchen & Bathroom is applied in accordance with the instructions for use. If mould growth occurs within 10 years of application we'll replace the paint free of charge to rectify the affected areas. This warranty is limited and excludes all labour and other charges.

✓ Interior ✓ Wall

**Precautions and Limitations**

Do not use at temperatures below 10 °C, or when the temperature of the surface may fall below 10 °C during the drying period. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 30 minutes, allow 7 days for the film to fully cure before washing.

Tinted Colours: Ensure that the paint is thoroughly shaken and stirred immediately after addition of tinter to the can and again before use.

**Performance Guide**

Weather <b>Designed for interior use only.</b>	
Heat Resistance <b>Softens and sticks to other painted surfaces over 70 °C</b>	Water <b>Suitable for use in wet areas.</b>
Solvent <b>Sensitive to aromatic hydrocarbons and alcohols.</b>	Abrasion <b>Good wet and dry burnish resistance and stain removal.</b>

Typical Properties			
Gloss Level <b>5 - 10 at 60 degrees</b>	Thinner <b>Water</b>		
Colour <b>Machine tinted to a wide range of colours off white base.</b>			
Dulux Colour Base <b>✓ Vivid White</b>			
Components <b>1</b>	Number of Coats <b>2</b>		
Toxicity <b>Lead free. Dry film is non-toxic</b>	V.O.C. Level <b>&lt;16g/L</b>		
Meets ECNZ V.O.C. Requirements? <b>Yes</b> Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.			
Touch Dry <b>30 Minutes</b>			
Clean Up <b>Water</b>			
Clean Up Description Clean all equipment with water			
Application Methods <b>Air Spray</b> <b>Airless Spray</b> <b>Brush</b> <b>Roller</b>			
Application Conditions	Solids by Volume		
	<input type="text" value="43"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="63"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="25"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text" value="2 Hours"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="16"/>

**Application Guide**

Surface Preparation

**Previously Painted Surfaces:**  
All surfaces must be thoroughly cleaned and free of all loose dirt, dust, grease, loose or flaking paint, and loose surface plaster. Existing mould must be treated prior to painting. Remove mould with Selleys® Rapid Mould Killer™ or by scrubbing with a scouring pad and bleach solution (1 part bleach to 3 parts water) - use gloves and goggles. Leave solution on the surface for 15 minutes then wash with clean water and wipe dry. Several applications may be necessary to remove stubborn mould blooms. Scrape and sand down any loose, peeling and flaking paint. Fill any cracks or holes with a suitable filler. Sand gloss and semi gloss finishes to a dull flat finish to allow a sound surface before top coating. Clean with a damp cloth, and then apply one coat of Dulux 1 Step Water Based to any areas which have been repaired or which have an uneven gloss level. Areas where paint has peeled, apply 1 coat of Dulux 1 Step Water Based.

**Bare Paperfaced Wallboard, Cement, Brick:**  
Brush down to remove any surface dust. Apply one coat of Dulux 1 Step Waterbased.

**Bare Interior Timber:**  
Sand smooth. Dust off. Apply one coat of Dulux 1 Step Waterbased.

**Bare Set Plaster, Fibrous Plaster, Plasterglass:**  
Brush down to remove any surface dust. Apply once coat of Dulux Precision Sealer Binder. For best results on bare set plaster and powdery surfaces apply one coat of Dulux Precision Sealer Binder.

**Application Procedure and Equipment**

Brush, roller and spray.

**BRUSH/ROLLER**  
Use medium nap roller (8 - 12mm). Pre-wet brushes and roller with water before commencing application. Avoid excessive brushing or rolling back into the paint which has been drying for more than 3 minutes. Thinning is not usually required. Under hot conditions application can be eased by thinning with up to 50mL water per litre and slightly dampening the surface. Apply two coats of Wash & Wear +Plus Kitchen & Bathroom Low Sheen ensuring that the first coat is completely dry before applying the second. Note, using poor quality or worn rollers can affect the final finish achieved. Some colours may require more than 2 coats, especially when painting over dark colours.  
Brush, roller, conventional and airless spray.

**AIRLESS/CONVENTIONAL SPRAY**  
Suitable for application by all standard spray equipment. If necessary, to aid atomisation, up to 100 ml per litre of water may be added for conventional spray or up to 30 ml per litre of water for airless spray. Use 0.015" to 0.017" spray tip at approximate pressure of 2200 - 2600 PSI.

**Health and Safety**

SDS Number <b>DLX001119</b>	SDS Link <a href="#">View SDS Link</a>
--------------------------------	---

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

**Transport and Storage**

Pack A <b>52A04912</b>	
Size: <b>1 Litre 2 Litre 4 Litre 10 Litre</b>	Weight: <b>1.4 Kg 2.8Kg 5.6Kg 13Kg</b>
Flash Point <b>NA</b>	UN Number <b>NA</b>
Dangerous Goods Class <b>NA</b>	Package Group <b>NA</b>

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.