

NZDU00426 Dulux Design Copper Patina Effect

Introduction

Product Code
690-D0102

Part B
690-D0101

Description and Image

Apply Dulux Copper Patina Effect over Copper Effect to create the green patination of aged copper.

Features and Benefits

- Apply with brush, cloth or sponge
- Create the green patination of aged copper
- Clean brushes and equipment with water

Uses

Apply over Dulux Copper Effect. Best results are achieved if treatment begins as soon as the final coat of Dulux Copper Effect is touch dry (approximately 2 hours) and within 12 hours of application.

Precautions and Limitations

Do not apply in high humidity, below 10°C or above 30°C.
Do not apply a clear sealer as this can remove or damage the effect, especially when new. The aged effect can be rubbed off when touched. We recommend natural weathering. On exterior surfaces, patination runoff may stain adjacent surfaces.
Please Note: Copper Effect treated with Copper Patina is a chemical reaction. Individual results may vary due to film thickness, methods used, time elapsed, ambient temperatures, substrate, etc.

Typical Properties

Thinner
Not recommended

Colour
Green coloured liquid solution

Components
1

Number of Coats
1-2

Touch Dry
2 hours (25°C, 50% RH)

Clean Up
 **Water**

Application Methods

 **Brush**

Apply with brush, cloth or sponge.

Application Conditions

	Min	Max	Recommended
Recoat Time (min/hours)	2 hours	12 hours	2 hours

Application Guide

Application Procedure and Equipment

Apply over Dulux Copper Effect. Best results are achieved if treatment begins as soon as the final coat of Dulux Copper Effect is touch dry (approximately 2 hours) and within 12 hours of application. Prepare surfaces as per Dulux Copper Effect label. Apply Dulux Copper Patina solution by brush or muslin in a random pattern. The aged effect will continue to develop over days and weeks. A second coat can be applied if required. Do not apply a clear sealer as this can remove or damage the effect, especially when new. Individual results will vary due to the application method and environment. The patina can be rubbed off when touched.

Health and Safety

SDS Number
DLX002636

SDS Link
[View SDS Link](#)

Using Safety Precautions

For further product or application advice or a Safety Data Sheet contact Dulux Customer Service AUST 13 23 77, NZ 0800 800 424. For special medical advice and emergencies call AUST 1800 033 111, NZ 0800 734 607. If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST: 131 126; NZ 0800 764 766).

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage	
Pack A 690-D0102	
Size: <input type="text" value="500 mL 1L"/>	Weight: <input type="text" value="680 g 1.31 kg"/>
Dangerous Goods Class Not dangerous goods. No special transport requirements.	
Pack B 690-D0101	
Size: <input type="text" value="500 mL"/>	Weight: <input type="text" value="624 g"/>
UN Number 3082	
Dangerous Goods Class DG 9. Classified as Dangerous Goods for transport by Road, Rail & Marine and for transport by Air.	

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.co.nz. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.