

## NZCA00078 Cabot's Deck Wash

### Introduction

Part A  
918W0185

### Description and Image

**Cabot's Deck Wash** is a timber maintenance wash for use in between coating applications. It is designed to refresh exterior timber decking and help remove dirt, dust and bird droppings making it the perfect everyday cleaning solution.



### Features and Benefits

- Timber maintenance wash.
- Refreshes exterior timber.
- Helps remove dirt, dust and bird droppings.

### Uses

Previously oiled or stained timber. Not suitable for bare timber.

### Precautions and Limitations

Not suitable for bare timber.  
Do not use this product within 2 weeks of coating deck.  
Use Cabot's Deck Clean to prepare timber prior to top coating.

**Typical Properties**

Heat Thinner  
**Water**

Clean Up



**Water**

Application Methods

Broom or brush

Typical Property Notes

**Coverage**

Diluted Deck Wash will cover up to 60sq. metres per litre.

**Application Guide**

Application Procedure and Equipment

1. Add one part Cabot's Deck Wash in to a plastic bucket prior to adding ten parts of water. Mix well to ensure foam is created.
  2. Apply generously to the timber with a broom. Scrub vigorously.
  3. Leave the solution on the timber for up to 10 minutes. Do not allow solution to dry out on timber.
  4. Rinse off the surface with water using a garden hose to ensure all solution has been washed off.
- Heavily soiled or very dirty timber may require repeat application.

**Note:** Do not use this product within 2 weeks of coating deck.

**Health and Safety**

SDS Number  
**DLXGHSEN000655**

SDS Link  
[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. Slippery when spilt; clean up immediately. Avoid contact with skin and eyes or breathing vapour and spray mist (dust).  
Wear waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use.

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

**Transport and Storage**

Line Shade/Pack A  
**918W0185**

Size:

1L

Weight:

1.2kg

**Please refer to the Safety Data Sheet for full safety, health and transportation information.**

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.com.au](http://www.duspecplus.com.au). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.