

## NZDU04278 Dulux Concrete & Paving Stage 1 Sealed Surface Cleaner

### Description and Image

Dulux Concrete & Paving Sealed Surface Cleaner cleans tough oil and grease stains, decontaminating non-porous concrete & paving surfaces. Thorough cleaning allows for optimum adhesion of the Concrete & Paving Stage 2 Sealed Surface Primer.



### Features and Benefits

- Cleans tough oil and grease stains
- Prepares sealed surfaces for coating

### Uses

Use on areas such as: Sealed surfaces such as concrete garage floors, driveways, paths, patios and steps. Only use in areas that you can power wash to allow for a thorough rinse off of the product.

Suitable substrates include: Concrete, including coloured, stencilled and pattern sealed concrete; exposed aggregate & pebbles; brick; unglazed terracotta or porous tiles; sandstone, limestone or other natural & engineered stone.

✓ Interior ✓ Exterior

**Precautions and Limitations**

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do Not paint at surface temperatures below 10°C or when the temperature of surface may fall below 10°C during the drying period.

Do Not paint at surface temperatures above 35°C or when the temperature may exceed 35°C during the drying period.

Do Not apply to pavement surfaces that have a gradient greater than 1:8 or slope of 7 degrees.

For surfaces greater than 1:8 or 7 degrees please refer to Dulux Help and Advice for assistance.

Avoid exposure to rain or water for a minimum of 1 hour after application.

Although film is generally dry to touch in 30 minutes, allow 24 hours before light foot traffic and 7 days before vehicular traffic.

To achieve optimal results when applying a coating to a surface, it is essential to prepare the surface appropriately. We recommend using Dulux Concrete & Paving Sealed Surface Cleaner (52ZD0184) along with a power washer that has a minimum pressure rating of 1200PSI and a heavy-duty bristle brush. This will ensure a thorough cleaning the surface, which is crucial step in preparing it for coating application.

Previously painted surfaces:

- A previously painted surface refers to a surface that has already been painted or coated with a layer of paint or coating material. When a concrete or paving surface has been previously painted, it is important to consider the condition of the existing coating before applying any new coating material. The surface may need to be cleaned, stripped, or sanded to remove any loose or peeling paint, and any areas of damage or deterioration may need to be repaired.

Non-porous surfaces:

A non-porous surface refers to a surface that does not allow water or other liquids to pass through it. non-porous surfaces have a low porosity, meaning they have very small or no open spaces or pores that can absorb water or other substances.

Examples of non-porous surfaces include:

- Sealed concrete: concrete surfaces that have been treated with a sealant or coating to create a barrier that prevents moisture from penetrating into the concrete.
- Porcelain or ceramic tiles: these types of tiles have a glazed surface that makes them non-porous and resistant to moisture.
- Epoxy coatings: epoxy coatings are applied to concrete surfaces to create a non-porous barrier that is resistant to moisture and chemicals.

FAQ Reference:

<https://www.dulux.com.nz/products/concrete-paving/faq>.

**Performance Guide**

<p>Weather Designed for interior and exterior use.</p>	<p>Salt This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, this system will be resistant against salt.</p>
<p>Heat Resistance This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, this system will have an upper heat resistance of 80oC.</p>	<p>Water This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats this system will be resistant against water. The system is not suitable for ponded water situation.</p>
<p>Solvent This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, the system is sensitive to aromatic hydrocarbons and alcohols.</p>	<p>Abrasion This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, this system will have good wet and dry burnish resistance and stain resistance.</p>
<p>Acid This product is to be used as a Sealed Surface Cleaner only when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, this system will be resistant against mild acids.</p>	<p>Alkali This product is to be used as a Sealed Surface Cleaner only; when it is topcoated with Dulux Concrete &amp; Paving Sealed Surface Primer and Dulux Concrete &amp; Paving water-based topcoats, this system will be resistant against mild alkalis.</p>

Typical Properties	
Gloss Level <b>Not applicable</b>	Thinner <b>Dilution ratio is 1:20 in water.</b> <b>For heavy stains, dilution ratio is 1:5 in water.</b>
Colour <b>Clear</b>	
Components <b>1</b>	Number of Coats <b>Not applicable</b>
Toxicity <b>Lead free. Dry film is non-toxic</b>	V.O.C. Level <b>Not applicable</b>
Shelf Life <b>2 years minimum from Date of Manufacture, in an unopened container.</b>	
Sanding Properties <b>Not applicable</b>	Mixing Ratio <b>Dilution ratio is 1:20 in water.</b> <b>For heavy stains, dilution ratio is 1:5 in water.</b>
Pot Life <b>Not applicable</b>	Touch Dry <b>Not applicable</b>
Clean Up  <b>Water</b>	
Clean Up Description Clean all equipment with water while wet. Do not attempt to recover dried out brushes or rollers.	
Typical Property Notes 1L will clean an area of up to 20m <sup>2</sup>	

## Application Guide

### Surface Preparation

To achieve optimal results when applying a coating to a surface, it is essential to prepare the surface appropriately. We recommend using Dulux Concrete & Paving Sealed Surface Cleaner (52ZD0184) along with a power washer that has a minimum pressure rating of 1200PSI and a heavy-duty bristle brush. This will ensure a thorough cleaning the surface, which is crucial step in preparing it for coating application.

#### **For previously painted and non-porous surfaces:**

On all surfaces, cleaning is the most important step. The concrete must be cleaned well and profile correctly.

1. Mask all adjacent surfaces to prevent acid and water splashing to areas that are not needed for the application.
2. Pressure wash the surface (use a 1200psi or higher-pressure machine) to remove dirt dust, algae, mould and other contaminants as well as possible.
3. Apply Dulux Concrete & Paving Sealed Surface Cleaner using a plastic watering can evenly apply, before scrubbing into the surface. Dulux Concrete & Paving Sealed Surface Cleaner contains both acid and surfactants. The latter are designed to help remove any oily residues in the surface.
4. Allow Dulux Concrete & Paving Sealed Surface Cleaner to remain on the surface for 10-15 minutes even though most reaction (seen as bubbling/fizzy reaction) will likely subside after a couple of minutes. Ensure that the surface does not dry out. Some reaction products from the acid may form insoluble residue. If this occurs and the surface dries these residues will be very hard to remove.
5. Power wash the surface to remove all residues released.
6. Allow the cleaned surface to dry.

#### **Combination surfaces (bare surface and sealed surface are present):**

1. Pressure wash the surface (use a 1200psi or higher-pressure machine) to remove dirt dust, algae, mould and other contaminants as well as possible
2. Apply Dulux Concrete & Paving Sealed Surface Cleaner using a plastic watering can evenly apply, before scrubbing into the surface. Allow Dulux Concrete & Paving Sealed Surface Cleaner to remain on the surface for 10-15 minutes even though most reaction (seen as bubbling/fizzy reaction) will likely subside after a couple of minutes. Ensure that the surface does not dry out.
3. Power wash the surface to remove all residues released.
4. Apply Dulux Concrete & Paving Bare Concrete Etch & Clean (52ZD0198), using a plastic watering can, to bare patches of concrete. Allow Dulux Concrete & Paving Bare Concrete Etch & Clean to remain on the surface for 10-15 minutes even though most reaction (seen as bubbling/fizzy reaction) will likely subside after a couple of minutes. Ensure that the surface does not dry out. Some reaction products from the acid may form insoluble residue. If this occurs and the surface dries these residues will be very hard to remove.
5. Power wash the surface to remove all residues released. Allow the cleaned surface to dry.

### Application Procedure and Equipment

#### **Application**

##### **For a Colour/Paint Finish:**

Stage 1: Clean the surface with Dulux Concrete & Paving Sealed Surface Cleaner

Stage 2: Apply 1 coat of Dulux Concrete & Paving Sealed Surface Primer (52ZD0200) and allow the surface to dry.

Stage 3: Apply any waterbased Dulux Concrete & Paving Stage 3 Finish. (Dulux Concrete & Paving Coloured Sealer - 52RD0152, 52ND0152, Dulux Concrete & Paving Super Grip - 52VD0153, Dulux Concrete & Paving Crushed Pebble Effect - 52WD0165, 52WD0173)

##### **For a Clear Finish:**

Stage 1: Clean the surface with Dulux Concrete & Paving Sealed Surface Cleaner.

Stage 2: No Dulux Concrete & Paving primers are required.

Stage 3: Apply Dulux Concrete & Paving Clear Protective Sealer (32QD0170, 32QD0175)

Health and Safety	
SDS Number <b>DLXNZ7EN003977</b>	SDS Link <a href="#">View SDS Link</a>
Using Safety Precautions Wear overalls, safety glasses and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variation in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking, or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.  Please refer to SDS Link. In case of emergency, please call 0800 220 770.	
<b>Please refer to SDS Link. In case of emergency, please call 0800 220 770.</b>	

Transport and Storage	
Pack A <b>1</b>	
Size: <input type="text" value="1L, 2L"/>	Weight: <input type="text" value="1.465KG, 2.300KG"/>
Flash Point <b>Not applicable - waterbased</b>	UN Number <b>Not applicable</b>
Dangerous Goods Class <b>Not classified as dangerous goods</b>	Package Group <b>Not applicable</b>

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.