

## NZDU00413 Dulux Precision Stain Smoke & Odour Blocker

### Introduction

Product Code  
**30SX383A**

### Description and Image

Dulux PRECISION Stain, Smoke & Odour Blocker is the professionals choice for a fast drying, superior stain blocker. It blocks a wide range of stubborn water & oil based stains, protects against tannin bleed in timber and seals odours. With excellent adhesion properties, it is suitable as a primer, sealer and undercoat. Suitable for use in interior & spot exterior applications

### Features and Benefits

- Shellac Based
- Fast drying
- Primes interior & spot exterior surfaces
- Forms a highly impervious film that seals stains & odours, including grease, smoke, tannin, graffiti & water stains
- Touch dry 15min, re-coat 45min
- Can be used under both oil and water based premium topcoats

### Uses

Plasterboard  
Bare timber  
Previously painted surfaces  
Timber  
MDF  
Aged enamel  
Masonry  
Cement sheet





### Precautions and Limitations

All preparation and painting must conform to AS/NZS 2311:2009 Guide to the painting of buildings. NB: This Standard provides a guide to products and procedures for the painting of buildings for general domestic, commercial and industrial use. The Standard does not include a specific recommendation for the long-term protection of iron or steel exposed directly to the atmosphere or to internal climates likely to have aggressive environments which are dealt with in AS/NZS 2312.

Do not apply if the surface temperature is below 10C or conditions indicate it will fall below 10C during the drying period.  
Do not apply if the surface temperature is above 35C or conditions indicate it will rise above 35C during the application period.

For stain blocking applications do not tint  
For stain blocking applications do not thin

| Performance Guide   |  |
|---|--|
| Weather<br><b>For interior use and ONLY spot exterior priming</b>   |  |
| Heat Resistance<br><b>Suitable for normal interior surface temperatures. The product remains permanently thermoplastic. Temperatures above 80C should be avoided.</b> | Water<br><b>Resists intermittent condensation and water splash</b> |
| Solvent<br><b>Sensitive to alcohol, ketone and acetate solvents. Resistant to Hydrocarbon solvents</b>  | Abrasion<br><b>Only to be used as a primer. May be sanded</b>      |
| Acid<br><b>Resistant to intermittent exposure to mild acids</b>   | Alkali<br><b>Sensitive to even mild alkaline materials</b>         |

| Typical Properties  |   |
|---|---|
| Gloss Level<br><b>Flat</b>  | Thinner<br><b>Methylated Spirits</b>  |
| Colour<br><b>White - Tinting is not recommended</b>   |   |
| Components<br><b>1</b>  | Number of Coats<br><b>1</b>   |
| Toxicity<br><b>Lead Free, Dry Film is non-toxic</b>   | V.O.C. Level<br><b>&lt;506g/l</b>   |
| Shelf Life<br><b>2 years from date of manufacture</b>   | Meets ECNZ V.O.C. Requirements?<br><b>No</b>  |
| Sanding Properties<br><b>Sandable when dry - 2 hours</b>  |   |
| Touch Dry<br><b>15 Minutes</b>  |   |
| Clean Up<br><br>Methylated Spirits  |   |
| Application Methods<br> <b>Air Spray</b>  <b>Airless Spray</b>  <b>Brush</b>  <b>Roller</b> |   |
| Stir well before use with a flat paddle using an up and down scooping action. Stir regularly during use. Precision Stain Smoke & Odour Blocker dries very quickly so Dulux recommends to cover brushes and rollers, cans and roller trays with an impermeable material (Cling Wrap) when the product is not being used for periods of duration greater than 20 minutes.   |   |
| Application Conditions  | Solids by Volume<br><input type="text" value="37.8"/>   |
|   | Min Max Recommended   |
| Wet Film Per Coat (microns)   | <input type="text" value="71"/> <input type="text" value="100"/> <input type="text" value="83"/>                        |
| Dry Film Per Coat (microns)   | <input type="text" value="27"/> <input type="text" value="38"/> <input type="text" value="32"/>                         |
| Recoat Time (min/hours)   | <input type="text" value="45 Minutes"/> <input type="text" value="Indefinite"/> <input type="text" value="45 Minutes"/> |

Theoretical Spread Rate (m<sup>2</sup>/L)

14

9.95

11.81

**Typical Property Notes**

Vehicle: - Shellac Resin

Weight Solids: - 60.4% (+/-) 2%

Volume Solids: - 37.8% (+/-) 2%

Weight per Litre (kg/Litre) : - 1.264 (+/-) 0.2

Viscosity: - Medium viscosity liquid

**Application Guide**

**Surface Preparation**

All surfaces must be thoroughly dry, clean and free of all loose dirt, surface chalk, grease, mould, mildew, wallpaper paste and wax, loose or flaking paint. New timber surfaces should be sanded smooth and dusted down prior to priming. Fill nail holes, imperfections and cracks with a suitable filler, sand and dust off. Spot prime the filled areas.

Avoid exposure to steam and condensation for 48 hours after application.

If washing is necessary, use a non-soapy detergent or Selseys Sugar Soap. Rinse well and allow to dry.

Peeling or Loose Paint: Scrape off loose paint and sand to a smooth surface. Sanding or removal of paint containing lead is hazardous.

Glossy Surfaces: For maximum adhesion, scuff sand the surface thoroughly before priming.

Mould or Mildew Covered Surfaces: Wash the area with a mildew remover, rinse with water and allow to dry before priming. Note: Precision Mould and Stain Blocker is recommended for mildew prone areas along with a topcoat designed for such areas.

Masonry, Brick, Stucco and Plaster: Precision Stain Smoke and Odour Blocker may be used on clean, dry, aged masonry surfaces that have cured (dried) for at least 28 days

**Application Procedure and Equipment**

Brush, roller, airless, conventional spray.

Stir contents thoroughly before and during use.

Apply one coat of Precision Stain Smoke & Odour Blocker. For heavily stained surfaces and paper-faced plasterboard where there is different texture between the paper and jointing compound or where extra filling and smoothness is required, apply a second coat. A full, continuous coat is essential to achieve adequate film build and to ensure no 'imperfections' which allow stains to bleed through.

Brush/Roller: Apply by brush or roller, full even coats direct from the container. Do not thin if used for stain blocking applications. For other applications, including adhesion priming of difficult surfaces, thin up to 50ml per litre of methylated spirits to ease application.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. Only if necessary should the product be thinned with Methylated Spirits to assist spraying when used for stain blocking applications. In such case do not exceed 50ml per litre. For other applications the paint can be thinned with up to 100ml per litre of methylated spirits to aid atomisation.

Clean brushes and rollers with methylated spirits prior to and after use.

**Health and Safety**

SDS Number

**DLXNZLEN001184**

SDS Link

[View SDS Link](#)

**Using Safety Precautions**

Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

| Transport and Storage                            |   |
|--|---|
| Pack A<br><b>30SX383A</b>                        |   |
| Size:<br><input type="text" value="4L 1L 350g"/> | Weight:<br><input type="text" value="5.41 Kg 1.40 Kg 0.43 Kg"/> |
| Flash Point<br><b>13C</b>                        | UN Number<br><b>1263</b>  |
| Dangerous Goods Class<br><b>3</b>                | Package Group<br><b>II</b>                                      |



**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.