

NZPR00109 Dulux Professional Quick Dry Primer Surfacer

Introduction

Product Code
361-97650

Description and Image

Dulux Professional Quick Dry Primer Surfacer is a premium alkyd based, non-inhibitive, primer surfacer with grain filling and sanding qualities. It can be used on interior or exterior surfaces as a primer surfacer for new or refurbishment work. All Dulux Professional products are designed to meet the application needs of painters.

Features and Benefits

- Grain filling
- Easy Sanding
- Blocks common stains
- Interior & exterior use
- Provides an even base for subsequent top coating.
- Reduces time & effort to produce a smooth surface
- Blocks stains from bleeding through and marring subsequent top coats.
- Multipurpose

Uses

Use Dulux Professional Quick Dry Primer Surfacer as a rapid dry interior or exterior primer surfacer over bare timber or previously painted areas. This product has excellent sanding and filling properties delivering a superfine even finish suitable for top coating.

Precautions and Limitations

Do not apply if the surface temperature is below 10C or conditions indicate it will fall below 10C during the drying period.

Performance Guide

Weather

Recommended for both interior & exterior use.

Heat Resistance

Up to 100C. Prolonged exposure to 100C heat will cause embrittlement.

Water





Excellent resistance to condensation and water splash as part of system.

Solvent

Resistant to alcohol & hydrocarbons. Film is liable to attack from strong solvents.

Abrasion

Good when topcoated.

Typical Properties			
Thinner Mineral Turpentine			
Colour White			
Components 1		Number of Coats 1	
Toxicity Lead free. Dry film is non-toxic.		V.O.C. Level 488 g/L	
Meets ECNZ V.O.C. Requirements? No			
Sanding Properties Excellent			
Touch Dry 1 Hour			
Clean Up  Thinner			
Clean Up Description Clean all equipment with mineral turpentine.			
Application Methods  Air Spray  Airless Spray  Brush  Roller			
Application Conditions		Solids by Volume	
		<input type="text" value="39"/>	
		Min	Max
Wet Film Per Coat (microns)	<input type="text" value="141"/>	<input type="text" value="141"/>	Recommended <input type="text" value="141"/>
Dry Film Per Coat (microns)	<input type="text" value="55"/>	<input type="text" value="55"/>	<input type="text" value="55"/>
Recoat Time (min/hours)	<input type="text" value="16 Hr"/>	<input type="text" value="3 Months*"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="7.09"/>	<input type="text" value="7.09"/>	<input type="text" value="7.09"/>
Typical Property Notes *Dulux Professional Quick Dry Primer Surfacer must be recoated within 3 months when fixed and exposed to the environment. Where there is any uncertainty of primer integrity, testing the adhesion of the primer to the timber is recommended. If any of the existing coating comes off, it is unsound and needs to be removed by sanding. If in any doubt sand the entire surface bare before painting.			

Application Guide

Surface Preparation

Ensure all surfaces are clean and dry prior to application. Brush down to remove dust. Stir well with a broad flat stirrer prior to application. Previously painted surfaces, must be sanded to remove loose, peeling, flaking or chalky paint. Sand all gloss and semi gloss surfaces to a dull finish and wipe down with a damp cloth to remove surface dust. Spot prime bare areas.

Application Procedure and Equipment

Brush, roller, or spray

Stir thoroughly before and during use with a broad flat paddle using an upward lifting motion. Apply by brush, roller, or spray. Thin with up to 50mL of mineral turpentine per litre if necessary.

Airless spray advice:
Tip size: 0.015-0.017"
Pressure: 2200-2800

Health and Safety

SDS Number
DLXNZLEN003166

SDS Link
[View SDS Link](#)

Using Safety Precautions

For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux NZ Sales and Customer Service offices.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Pack A
361-97650

Size:

4 Litre 10 Litre

Weight:

5.6 Kg 13.8 Kg

Flash Point

32C

UN Number

1263

Dangerous Goods Class

3b

Package Group

III

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.