

NZCA00019 Cabot's Garden Furniture Oil Water Based

Introduction

Part A
847-line

Description and Image

Cabot's Garden Furniture Oil Water Based is a highly durable, low odour exterior oil. It is designed to provide exceptional durability to garden furniture, BBQ trolleys and benches and lasts longer than traditional garden furniture oils. Garden Furniture Oil Water Based's advanced dual technology allows natural oils to penetrate and nourish the timber, then creates a durable acrylic barrier for a beautiful natural finish.



Features and Benefits

- Advanced Dual Technology.
- UV protection.
- Water repellent.
- Dirt and mould resistant.
- Fast recoat.
- Allows natural oils to penetrate and nourish the timber then creates a durable acrylic barrier.
- Blocks out harmful UV rays preventing them from penetrating and damaging the surface while resisting colour fading.
- Penetrates the timber and forms a water repellent barrier aiding protection against mould and minimises cracking and splitting.
- Contains powerful ingredients to resist the growth of wood staining mould while providing excellent dirt and stain resistance.
- Recoat after only 2 hours.

Uses

Exterior timber projects including garden furniture, BBQ trolleys and benches.

Precautions and Limitations

Do not apply this product in temperatures below 10°C or above 35°C, or when rain or heavy dew is expected during the drying period. In hot temperatures do not apply in direct sunlight, cool the timber by lightly dampening with water and coat in the shade.

Performance Guide

Weather Excellent.	Salt Good.
Heat Resistance Up to 70 degrees Celsius. Higher temperatures will cause film to soften.	Water Excellent.

Typical Properties			
Gloss Level Matt			
Colour 3 packaged colours			
Components 1		Number of Coats 2	
Toxicity Lead-free		V.O.C. Level < 40g/L	
Touch Dry 1 hour			
Clean Up  Water			
Application Methods  Brush			
Application Conditions	Solids by Volume 15		
Wet Film Per Coat (microns)	Min	Max	Recommended 87
Dry Film Per Coat (microns)			13
Recoat Time (min/hours)	2 hours		
Theoretical Spread Rate (m ² /L)			12
Typical Property Notes Spreading rate Approximately 12 square metres per litre depending on the porosity and condition of the timber.			
Drying and re-coat time All timings quoted at 25C and 50% humidity. Cooler or humid conditions may require longer.			

Application Guide

Surface Preparation

Note fill holes and imperfections with a suitable timber putty.

Bare timber

To coat new bare timber immediately, scrub damp timber with Cabot's New Timber Prep, following label instructions. New Timber Prep will draw out tannins and oils quickly from the surface, allowing you to skip the 4-6 weeks weathering process required for new timber. Always follow New Timber Prep with Cabot's Deck Clean following label instructions.

Previously painted or varnished timber

Remove back to bare timber using a paint stripper, or sanding. For exterior surfaces clean with Cabot's Deck Clean following label instructions.

Previously stained or oiled timber

For exterior surfaces clean with Cabot's Deck Clean following label instructions, then allow timber to fully dry. Test if the surface is ready for coating by sprinkling water on the timber. If the water beads on the surface, repeat the application of Cabot's Deck Clean. If water is absorbed into timber, it is ready for coating. For a more transparent look, sand timber back to bare before coating.

Weathered and grey timber

For best results, sand timber back to fresh substrate. Clean with Cabot's Deck Clean following label instructions.

Application Procedure and Equipment

Stir thoroughly with a broad flat paddle before and during use. Apply liberally along the length of the timber including exposed edges and end grain, by brush. The initial milky colour helps with even product application, drying to a semi-transparent finish. Apply two coats allowing 2 hours between coats.

Maintenance

Re-apply as the timber changes colour or when water repellency diminishes due to weathering. Follow surface preparation instructions.

Health and Safety

SDS Number

22379

SDS Link

[View SDS Link](#)

Using Safety Precautions

Keep out of reach of children. Avoid skin and eye contact. Provide adequate ventilation. If using inside keep windows and doors open during application and drying time.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Line Shade/Pack A

847-line

Size:

Weight:

1L

1.2Kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.