

## NZIN00042 Intergrain UltraPrep Tannin & Oil Remover

### Introduction

Part A  
552W0103

### Description and Image

**Intergrain UltraPrep™ Tannin & Oil Remover** is a powerful, high strength remover. Specially formulated to quickly draw out tannins and oils from the surface of exterior timber. The high strength formula also lifts old or worn existing timber finishes.

Note: Intergrain UltraPrep Tannin & Oil Remover is not a paint and varnish stripper, to remove sound coatings use a coatings stripper or sand off.



### Features and Benefits

- High strength
- Draws out tannins and oils from the timber surface
- Lifts old or worn existing timber finishes

### Uses

On all exterior timber including decking, outdoor furniture, cladding, screening and fences.  
Not suitable for interior applications.

### Precautions and Limitations

Exterior use only. Not suitable for interior use.  
Wear waterproof gloves and safety glasses.  
Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be cleaned.  
May be corrosive to metals. Rinse off thoroughly if contact occurs.  
You must always use UltraPrep Timber Cleaner after UltraPrep Tannin & Oil Remover.

### Typical Properties

V.O.C. Level

<5g/L

Meets ECNZ V.O.C. Requirements?

**Yes**

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tint required for non-factory packaged colours.

Clean Up



**Water**

Application Methods

Stiff bristle brush.

Application Conditions

	Min	Max	Recommended
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text"/>	<input type="text" value="10"/>	<input type="text"/>

Typical Property Notes

Use undiluted.

**Coverage**

Up to 10m<sup>2</sup>/L

## Application Guide

### Surface Preparation

Remove surface dirt by sweeping or washing down with water.

### Application Procedure and Equipment

Shake Intergrain UltraPrep Tannin & Oil Remover thoroughly.

Wet the timber surfaces to be cleaned with water.

Apply Intergrain UltraPrep Tannin & Oil Remover undiluted to the timber with a stiff bristle brush. Spot cleaning should be avoided to prevent patchy results.

**Note:** Product is very slippery, take care when walking on treated surface.

Leave Intergrain UltraPrep Tannin & Oil Remover on the timber for 10–15 minutes. If necessary, apply more product to keep timber damp throughout this period. Do not allow to dry on the surface.

Scrub the timber vigorously with a stiff broom. Do not use a wire brush.

Rinse off exterior surfaces thoroughly using maximum pressure from a garden hose or using a high pressure water cleaner. For best results, a high pressure water cleaner is recommended. Important: Failure to thoroughly remove Intergrain UltraPrep Tannin & Oil Remover may result in timber discolouration under clear finishes.

If removing worn coatings and stubborn areas remain, sand or repeat application as per the instructions above.

Clean timber with Intergrain UltraPrep Timber Cleaner closely following label instructions

**Note:** After cleaning with Intergrain UltraPrep Tannin & Oil Remover, some timber species will appear darker. Intergrain UltraPrep Timber Cleaner will restore brightness.

**Caution:** Wear waterproof gloves and safety glasses. Avoid contact with painted, glass, concrete or metal surfaces and vegetation. Protect areas not to be treated. May be corrosive to metals. Rinse off thoroughly if contact occurs.

### Help & advice

Australia – 1800 630 285  
[www.intergrain.com.au](http://www.intergrain.com.au)

NZ – 0800 222 687  
[www.intergrain.co.nz](http://www.intergrain.co.nz)

For detailed project specifications or a Safety Data Sheet, contact Intergrain Help & Advice or visit our website.

## Health and Safety

SDS Number

**DLXGHSEN003476**

SDS Link

[View SDS Link](#)

### Using Safety Precautions

Causes severe skin burns and serious eye damage. May cause respiratory irritation.

Do not breathe fume, mist, vapours or spray. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and a suitable respirator as required. Wash contaminated clothing before reuse. Wash hands, face and all exposed skin thoroughly after handling. Keep container tightly closed. Store locked up. Store in a well ventilated place, away from foodstuffs, oxidising agents and acids. Do not empty into drains. Slippery when spilt

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

Transport and Storage	
Line Shade/Pack A <b>552W0103</b>	
Size:	Weight:
<b>1L 4L 10L</b>	<b>1.14 4.39 11.23</b>
<b>Please refer to the Safety Data Sheet for full safety, health and transportation information.</b>	

#### Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.