

NZPP00025 Porter's Paints Stucco Wax

Introduction

Part A
PZ5-P1201

Description and Image

Porter's Stucco Wax is a superb blend of fine waxes especially formulated to be used as a protective finish over Porter's Fresco, Chalk Emulsion and Interior Distemper where improved durability is required.

Features and Benefits

- Dries to a hard finish.
- Can be buffed to achieve required gloss.
- Appears creamy white in can, dries clear.
- Protects and polishes furniture painted with Porter's Chalk Emulsion.
- Adds a fine polished finish to Porter's Fresco.

Uses

Interior. Can be applied as a protective finish over Porter's Fresco, Porter's Chalk Emulsion and Porter's Interior Distemper, or on it's own on timber furniture when a fine waxed finish is required.

✓ **Interior**

Precautions and Limitations

Please be aware that Stucco Wax may make the applied paint colour appear darker.
Not suitable for use in wet areas.
Do not apply in high humidity, below 10°C or above 30°C.

Typical Properties

Thinner

Soluble in Organic solvents. Insoluble in Water

Colour

Off-White in can, dries to a clear finish.

Components

1

Number of Coats

1

Touch Dry

30 minutes

Clean Up

Pure gum turpentine.

Application Methods



Trowel

USE A SPATULA OR TROWEL to apply Stucco Wax sparingly, straight from the can, or USE A SOFT LINT FREE CLOTH.

Application Conditions

Solids by Volume

0

Min

Max

Recommended

Recoat Time (min/hours)

12 hours

Theoretical Spread Rate (m²/L)

10

12

10

Application Guide

Surface Preparation

Complementary products:

Porter's Stucco Wax is compatible for use over Porter's Interior Distemper, Porter's Chalk Emulsion and Porter's Fresco. Test before use as a slight colour variation may occur.

Application Procedure and Equipment

Do not apply paint if Relative Humidity is above 85% or temperature is within 3°C of Dew Point.

Do not apply if the surface temperature is greater than 30°C or below 10°C, or likely to fall below 10°C during the application or drying period.

Use either of the following methods:

Use A spatula or trowel to apply Stucco Wax sparingly, straight from the can, or use a soft lint free cloth.

In both instances ensure Stucco Wax is sparingly and evenly applied.

Before the wax is completely dry buff vigorously by hand with a soft clean cloth, or mechanically with a lamb's wool buffer.

Walls will be touch dry after buffing, and completely dry after 12 hours. For best results, buff again the following day when the wax has hardened completely.

Application tip: Apply and buff small areas at a time. If the wax is allowed to dry out completely before buffing the job will be very much harder.

Health and Safety

SDS Number
DLXTOLEN001346

SDS Link
[View SDS Link](#)

Using Safety Precautions
Avoid breathing mist, vapours or spray. Use only outdoors or in a well ventilated area.
Keep out of reach of children. Read the label before opening or using.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Pack A
PZ5-P1201

Size:

225g, 850g & 3.3 Kg

Weight:

225g, 850g & 3.3 Kg

Flash Point
32

UN Number
1299

Dangerous Goods Class
3

Package Group
III

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.co.nz. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.