

NZPR00110 Dulux Professional Ultra 5 Surfacer, Prep & Finish

Introduction

Product Code
664-97583

Description and Image

Previously known as DULUX PROFESSIONAL Ultra 5 Surfacer, Prep & Finish
DULUX PROFESSIONAL Ultra 5 Surfacer, Prep & Finish is a 100% acrylic low VOC surface preparation specially designed to be an important component in achieving a Level 5 finish on new or pre-painted interior plasterboard surfaces.

Features and Benefits

- Aid to achieve a Level 5 finish
- High film build
- Versatile
- Water based
- Sands easily
- Consistent coverage
- Minimises problems of porosity difference between joints and substrate.
- Achieves high film build without running or sagging.
- May be tinted to light colours for use as a ceiling finish coat in dry areas.
- Easy clean up, low odour.
- Gives a better, smoother finish with less effort.
- Hides minor surface imperfections and promotes improved paint flow.

Uses

Use DULUX PROFESSIONAL Ultra 5 Surfacer, Prep & Finish where a good quality, professional finish is required. This product is suitable for use on paperfaced plasterboard, interior concrete, fibre cement sheet, solid plaster and pre-painted areas.

Precautions and Limitations

Do not apply if temperature is under 10°C, or when temperature of surface may fall below 10°C during the drying period, otherwise film formation will not be complete and a fall-off in properties will result.
For all walls and when product is used in bathrooms and other wet areas DULUX PROFESSIONAL Ultra 5 Surfacer, Prep & Finish must be top-coated with the appropriate DULUX finish coat.
Where accurate colour reproduction is required DULUX PROFESSIONAL Ultra 5 Surfacer, Prep & Finish must be top-coated with the appropriate DULUX finish coat.
When coating paper-faced wallboard that has aged and yellowed DULUX recommends that the surface be sealed with DULUX Prepcoat Sealer Binder.
For fibrous plaster surfaces DULUX recommends that the surface be sealed with DULUX Prepcoat Sealer Binder.
As with all higher build water borne coatings, best drying is obtained when there is a reasonable airflow over the coated surface.

Performance Guide

Weather




Not recommended for exterior use.

Heat Resistance
Up to 70°C.

Water
Excellent when topcoated with approved topcoat.

Solvent
Sensitive to aromatic hydrocarbons, alcohols and ketones.

Abrasion
Good when topcoated.

Typical Properties			
Thinner Thinning is not recommended.			
Colour White.			
Components 1		Number of Coats 1	
Toxicity Lead free. Dry film is non-toxic.		V.O.C. Level 3 g/L	
Touch Dry 2 Hours			
Clean Up  Water			
Clean Up Description Clean all equipment with water.			
Application Methods  Air Spray  Airless Spray			
Application Conditions	Solids by Volume		
	<input type="text" value="40"/>		
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="338"/>	<input type="text" value="338"/>	<input type="text" value="338"/>
Dry Film Per Coat (microns)	<input type="text" value="135"/>	<input type="text" value="135"/>	<input type="text" value="135"/>
Recoat Time (min/hours)	<input type="text" value="4 Hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="3"/>	<input type="text" value="3"/>	<input type="text" value="3"/>

Application Guide
<p>Surface Preparation</p> <p>All surfaces must be thoroughly clean and free of all loose dirt, grease, mould, mildew and wax, surface chalk and loose or flaking paint, efflorescence and loose surface plaster. Sand smooth and dust down. Prepare surface in accordance with the requirements of the chosen system.</p>
<p>Application Procedure and Equipment</p> <p>Conventional or airless spray. Airless Spray: Should be applied using a "cross-hatch" method to produce a film build of 150 to 200 microns. This involves holding the gun approximately 600mm from the wall and spraying an even coat horizontally across the substrate with a 50% overlap. Spraying on the next coat vertically completes application. An airless sprayer capable of applying 3.0 litres per minute at the pressure of 3300psi through a 21 to 27 thou tip with a 3/8 inch hose fitting should be used. Similar to the Graco 695 model. A 60 mesh in-line filter can be used. DO NOT USE FINE PAINT FILTERS. Sanding: Sand to a smooth surface free of any sign of peel or texture with 180 to 220 grit sandpaper. Stir contents thoroughly before and during use. Apply direct from the can. May be applied to dampened surfaces.</p>

Health and Safety	
<p>SDS Number DLXNZ7EN001906</p>	<p>SDS Link View SDS Link</p>
<p>Using Safety Precautions For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux Sales and Customer Service offices.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 0800 220 770.</p>	

Transport and Storage	
<p>Pack A 664-97583</p>	
<p>Size: <input type="text" value="10 Litre"/></p>	<p>Weight: <input type="text" value="16.1 kg"/></p>
<p>Flash Point NA</p>	<p>UN Number NA</p>
<p>Dangerous Goods Class NA</p>	<p>Package Group NA</p>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.