

NZDU00398 Dulux PREP WASH

Introduction

Product Code
951-82195

Description and Image

Dulux Prep Wash is an essential preparation product designed to obliterate dirt and mould, mildew and algae from new and old exterior surfaces prior to applying paint systems. It is effective in removing mould and other contaminants, cleaning and preparing the surface for coating. It also whitens stains and grey weathered timber.

Features and Benefits

- Contains mildewcide
- Supplied as concentrate
- Removes algae etc
- Removes dirt and grease stains
- Combats mould, mildew and algae
- Easy to use
- Prepares surfaces for painting

Uses

Cleaner that prepares all exterior surfaces for coating. Suitable surfaces: Timber, weatherboards, concrete, roof and other surfaces that are to be repainted. Not suitable to remove coatings.
Do not allow to come into contact with powder coated surfaces. Protect plants, bushes, metal and paint work that is not to be cleaned, with plastic sheets. Rinse off immediately and thoroughly if contact occurs. If contact with glass occurs, rinse thoroughly immediately. DO NOT mix with acids, bleach products, or other household cleaners.

Precautions and Limitations

Protect plants, bushes, metal and paint work that is not to be cleaned, with plastic sheets. Rinse off immediately and thoroughly if contact occurs. If contact with glass occurs, rinse thoroughly immediately. DO NOT mix with acids, bleach products, or other household cleaners.
Do not allow to come into contact with powder coated surfaces and other coated surfaces not to be repainted.
Note: Surface may be slippery while wet (roof).

Typical Properties			
Thinner	Water		
Colour	Pale yellow		
Components	1		
Mixing Ratio	1:1 with water		
Touch Dry	15-20 Minutes.		
Clean Up	 Water		
Clean Up Description	Clean up all equipment with water. Do not contaminate storm water with product or product washings.		
Application Methods	 Brush		
Broom Garden sprayer			
Application Conditions			
	Min	Max	Recommended
Wet Film Per Coat (microns)	0		0
Dry Film Per Coat (microns)	0	0	0
Recoat Time (min/hours)	n/a	n/a	n/a
Theoretical Spread Rate (m ² /L)	6	12	

Application Guide**Surface Preparation**

Remove any extreme caked dirt/mud with a waterblaster before using Dulux Prep Wash.

Test on a small inconspicuous area at recommended dilution to determine effectiveness and strength required.

Note: Wear protective gloves and goggles when using this product. Dulux Prep Wash is not a paint remover; however it may remove some old and weathered coatings. This product may not be able to remove hard water deposits, mould or mildew from old grout or silicone caulking.

Precaution: Protect plants, bushes, metal and paint work that is not to be cleaned, with plastic sheets. Rinse off immediately and thoroughly if contact occurs. If contact with glass occurs, rinse thoroughly immediately. DO NOT mix with acids, bleach products, or other household cleaners.

Application Procedure and Equipment

Apply by broom or brush. Or by garden sprayer.

1. Add one part Dulux Prep Wash concentrate to one part water in a clean plastic bucket and mix well.
2. Test on a small inconspicuous area at recommended dilution to determine effectiveness and strength required.
3. Apply diluted Dulux Prep Wash solution to walls/roof/trim with a broom/brush or garden sprayer. Leave the solution on the surface until mould and mildew stains disappear or soften (approximately 10 minutes), avoiding allowing the solution to dry out. Scrub vigorously.
4. Rinse off the surface with water using a high pressure or garden hose and allow surface to dry. Surface may be slippery while wet (roof). Stubborn stains may require longer time, more vigorous scrubbing, or additional treatment. Severely stained surfaces may need a power washer, or treatment with undiluted Dulux Prep Wash concentrate.

Health and Safety

SDS Number
000000022880

SDS Link
[View SDS Link](#)

Using Safety Precautions

For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Customer Service on 0800 800 424.

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Pack A
951-82195

Size: **1 L 5 L** Weight: **1.065 Kg 5.325 Kg**

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.