

NZPR00061 Dulux Professional Fast Finish Dry Fall Ceiling Black Flat

Introduction

Line Shade
56B-D0062

Description and Image

A flat, premium, waterbased ceiling paint designed specifically for spray application.

It is formulated with DryFall properties which, when applied to ceilings of minimum 2.7metres in height, dries to a powder and falls to the ground for easy clean up.



Features and Benefits

- Optimised for spray applicaiton
- Dry Fall properties
- Fast Finishing
- Excellent coverage
- Easy Clean Up

Uses

Ceilings (min 2.7m in height)

✓ Interior ✓ Ceiling

Precautions and Limitations

This product can neither cause nor prevent or cure the growth of mould, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.



Limitations

- Not for exterior exposure
- Not for high abuse surfaces
- Not for high corrosion areas
- Not for areas with high humidity*

*As High humidity can effect the Dryfall characteristics of this product, Dulux recommends that precautionary steps should be taken to cover flooring and/or furniture to protect from overspray or dust, when the Rel. Humidity during application exceeds or is likely to exceed 50%. At Rel. Humidity level exceeding 70% these precautions will become mandatory.

Caution: The standard height for ceilings in a Project Home is 2.4m. The overspray dust falling in these circumstances may not be completely dry.

Performance Guide	
Weather Designed for Interior use only, on ceilings minimum 2.7 metres in height.	
Heat Resistance Up to 70C	Water Not suitable for areas of high humidity.
Solvent Sensitive to aromatic hydrocarbons and alcohols.	Abrasion Not suitable for high abrasion areas.

Typical Properties	
Gloss Level 0 - 3 at 85 degrees	Thinner Water, but not recommended.
Colour Black	
Components 1	Number of Coats 2
V.O.C. Level 26 g/L	
Touch Dry 15 mins	
Clean Up  Water	
Clean Up Description Clean all equipment with water.	
Application Methods  Airless Spray	
Application Conditions	Solids by Volume <input type="text" value="40"/>
	Min Max Recommended
Wet Film Per Coat (microns)	<input type="text" value="83"/> <input type="text" value="125"/> <input type="text" value="83"/>
Dry Film Per Coat (microns)	<input type="text" value="33"/> <input type="text" value="50"/> <input type="text" value="33"/>
Recoat Time (min/hours)	<input type="text" value="2 Hours"/> <input type="text" value="Indefinite"/> <input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text" value="8"/> <input type="text" value="12"/> <input type="text" value="12"/>

Application Guide
<p>Surface Preparation</p> <p>Ensure all surfaces are clean and dry prior to application. Brush down to remove dust.</p> <p>Previously painted surfaces (except cement sheet) must be sanded to remove all loose, powdery and flaking paint. Wash down with sugar soap and rinse with clean water to remove any dirt, oil or grease. Treat any mould present on the surface with a bleach solution diluted 3 to 1 with water, then wash again with fresh water. Sand all gloss & semi-gloss surfaces to a dull finish. Fill any cracks or holes with a suitable filler, sand and dust off. No primer/undercoat required on most surfaces. Bare Steel should be prepared by applying a suitable metal primer.</p>
<p>Application Procedure and Equipment</p> <p>Stir well before use with a wide (approx 25mm) flat stirrer in a circular, lifting motion. Apply two coats by airless spray allowing at least two hours drying time between coats.</p> <p>Airless Spray Advice: Tip size: 0.015–0.019" Pressure: 2000–2400psi This coating is intended to be applied without thinning or diluting under normal environmental and application conditions.</p>

Health and Safety	
<p>SDS Number DLXNZ7EN002760</p>	<p>SDS Link View SDS Link</p>
<p>Using Safety Precautions</p> <p>Keep out of reach of children. Provide adequate ventilation.</p> <p>Keep windows and doors open during use and while drying. If spraying follow equipment guidelines and wear a suitable respirator.</p>	
<p>Please refer to SDS Link. In case of emergency, please call 0800 220 770.</p>	

Transport and Storage	
<p>Pack A 56B D0062</p>	
<p>Size: 15 Litres</p>	<p>Weight: 22.8 Kg</p>
<p>Flash Point NA</p>	<p>UN Number NA</p>
<p>Dangerous Goods Class NA</p>	<p>Package Group NA</p>

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.