

## NZDU00448 Dulux Ceiling White +Plus Kitchen & Bathroom

### Introduction

Product Code  
**615D0118**

Approvals  
**Environmental Choice Certified.**

### Description and Image

DULUX Ceiling White +PLUS Kitchen & Bathroom is an advanced whole-of-home ceiling formulation with Mouldshield® protection. It is tintable to light colours and has superior opacity to provide excellent hiding power, making it perfect for the whole home.

### Features and Benefits

- Water based
- Flat finish
- Excellent hiding power
- Mould & bacteria resistant formula
- Tintable to light colours
- Easy application
- Same day recoat & easy clean up
- One coat over light colours

### Uses

DULUX White Ceiling +PLUS Kitchen & Bathroom can be used on all interior ceilings where a flat finish is required.

### Precautions and Limitations

Do not exceed recommended spreading rate. Avoid exposure to steam and condensation for 48 hours after application. Although the film is dry to touch in 20 minutes, allow 7 days for the film to fully cure before lightly cleaning with a sponge wet with detergent solution.  
Do not paint at temperatures below 10 C or when the temperature of surface may fall below 10 C during the drying period.






### Performance Guide

Weather  
**Not suitable for exterior application.**

Heat Resistance  
**Up to 60 C**

Water  
**For interior use in damp and dry areas.**

Solvent  
**Poor solvent resistance.**

Typical Properties			
Gloss Level <b>Flat</b>		Thinner <b>Water</b>	
Colour <b>White</b>			
Components <b>1</b>		Number of Coats <b>2</b>	
V.O.C. Level <b>&lt;50 g/L</b>			
Touch Dry <b>20 minutes</b>			
Clean Up  <b>Water</b>			
Application Methods  <b>Air Spray</b>  <b>Airless Spray</b>  <b>Brush</b>  <b>Roller</b>			
Application Conditions		Solids by Volume	
		<input type="text" value="27"/>	
	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="83"/>
Dry Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	<input type="text" value="36"/>
Recoat Time (min/hours)	<input type="text" value="2 hours"/>	<input type="text" value="Indefinite"/>	<input type="text"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text"/>	<input type="text"/>	<input type="text" value="12"/>

## Application Guide

### Surface Preparation

#### PREVIOUSLY PAINTED SURFACES

Wash down with sugar soap and rinse with clean water to remove any dirt, oil, or grease. Scrape and sand down any loose, peeling and flaking paint. Fill any cracks or holes with a suitable filler. Sand gloss and semi gloss finishes to allow a sound surface before top coating. Dust off. Apply one coat of Dulux Prepcoat Acrylic Sealer Undercoat or Dulux 1 Step Water Based to any areas which have been repaired or which have an uneven gloss.

#### BARE PAPERFACED WALLBOARD, CEMENT, BRICK

Brush down to remove all surface dust. Apply one coat of Dulux Prepcoat Acrylic Sealer Undercoat or Dulux 1 Step Water Based.

#### BARE INTERIOR TIMBER

Sand smooth. Dust off. Apply one coat of Dulux 1 Step Water Based.

#### BARE SET PLASTER, FIBROUS PLASTER, PLASTERGLASS

Brush down to remove any surface dust. Apply one coat of Dulux 1 Step Oil Based. For best results on bare set plaster and powdery surfaces apply one coat of Dulux Sealer Binder.

### Application Procedure and Equipment

Brush, roller, conventional and airless spray.

Stir contents thoroughly before and during use with a broad flat stirrer using an upward lifting action.

Brush/Roller: Apply full even coats direct from container. If necessary, thin with up to 50 ml water per litre to assist application. Avoid rolling back over nearly dried sections.

Airless/Conventional Spray: Suitable for application by all standard spray equipment. Up to 50 ml water per litre may be added to aid atomisation.

## Health and Safety

### SDS Number

**DLXNZLEN002618**

### SDS Link

[View SDS Link](#)

### Using Safety Precautions

For detailed information refer to the product label and the current Material Safety Data Sheet available through Dulux NZ Sales and Customer Service offices.

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

## Transport and Storage

### Pack A

**615D0118**

### Size:

**4 Litre 10 Litre**

### Weight:

**5.7 Kg 14.3 Kg**

### Flash Point

**NA**

### UN Number

**NA**

### Dangerous Goods Class

**NA**

### Package Group

**NA**

**Disclaimer**

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.