

## NZDU00399 Dulux House Wash

### Introduction

Product Code  
**972-65004**

### Description and Image

Dulux House Wash is an all purpose cleaner for use on all exterior painted surfaces including weatherboards, timber, and concrete. It is designed to effectively clean coated surfaces to maintain any painted surface and keep it looking 'nice'. Contains d-Limonene, a natural extract from orange skins, to cut through grease and grime leaving surfaces sparkling clean with a fresh citrus fragrance.

### Features and Benefits

- Contains d-limonene
- Supplied as concentrate
- Cuts through grease and grime
- Effective cleaning solution
- Easy to use
- Pleasant citrus fragrance
- Maintenance of a painted surface

### Uses

All purpose exterior paint surface cleaner. Suitable surfaces: All washable hard surfaces (including roofs). Not suitable for bare timber or coatings less than 72 hours old. Do not allow to come into contact with powder coated surfaces.

### Precautions and Limitations

Note: Do not allow to come into contact with powder coated surfaces.  
Not suitable for bare timber or coatings less than 72 hours old.  
Note: Surface may be slippery while wet (roof).

### Performance Guide

Weather  
•

### Typical Properties

Thinner  
**Water**

Colour  
**Orange**

Components  
**1**

Mixing Ratio  
**50 mLs ((2 capfuls) to 1 Litre of water**

Touch Dry  
**20-30 Minutes.**

Clean Up



**Water**

Clean Up Description

Clean up all equipment with water. Do not contaminate storm water with product or product washings.

Application Methods



**Pad**

Mop/Sponge/Cloth

Application Conditions

	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text" value="0"/>	<input type="text" value="0"/>	<input type="text" value="0"/>
Dry Film Per Coat (microns)	<input type="text" value="0"/>	<input type="text" value="0"/>	<input type="text" value="0"/>
Recoat Time (min/hours)	<input type="text" value="n/a"/>	<input type="text" value="n/a"/>	<input type="text" value="n/a"/>
Theoretical Spread Rate (m <sup>2</sup> /L)	<input type="text" value="15"/>	<input type="text" value="20"/>	<input type="text"/>

## Application Guide

### Surface Preparation

Dulux House Wash should not be used on fresh coatings that are less than 72 hours old. Remove any excessive caked dirt/mud with a waterblaster before using Dulux House Wash.

Remove any moss/mould/mildew/lichen with Dulux Prep Wash before using Dulux House Wash.

For diluted solutions test effect on a non critical area before application to any paint surface.

Dulux House Wash will not remove coatings.

### Application Procedure and Equipment

1. Add approximately 50 mLs of Dulux House Wash concentrate (2 capfuls) to 1 Litre of water in a clean bucket and mix well.
  2. Apply diluted Dulux House Wash solution to walls/roof/trim with a mop/sponge/cloth to loosen grime and dirt. Do not flood the area with cleaning solution.
  3. Return excess solution to a bucket, then rinse with clean water or wipe off with a damp cloth and allow surface to dry.
- For stubborn stains and grease marks: Leave diluted solution on for up to 30 seconds and then wipe off with a damp cloth.
- For extra dirty areas: Increase the amount of Dulux House Wash concentrate to 250 mL per litre of water dilution. Avoid direct application of undiluted Dulux House Wash concentrate on old or painted surfaces as damage may occur.

## Health and Safety

SDS Number  
**000000022881**

SDS Link  
[View SDS Link](#)

### Using Safety Precautions

For detailed information refer to product label and the current Material Safety Data Sheet available through Dulux Customer Service on 0800 800 424.

**Please refer to SDS Link. In case of emergency, please call 0800 220 770.**

## Transport and Storage

Pack A  
**972-65004**

Size:

**1 L**

Weight:

**1.02 Kg**

## Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from [www.duspecplus.co.nz](http://www.duspecplus.co.nz). Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS/ NZS 4361 Parts 1 and 2 and Worksafe Australia or New Zealand guidelines.