NZDU00332 Dulux Prepcoat Acrylic Sealer Undercoat

Introduction

Line Shade
63052934

Approvals
Eco Choice Aotearoa Licensed Product

Description and Image

Dulux Acrylic Sealer Undercoat is suitable for all interior surfaces. It is especially designed for sealing and undercoating interior masonry and paperfaced wallboard. Dulux Acrylic Sealer Undercoat's unique Ultrasmooth™ Technology helps to eliminate the traditional problems of surface imperfections, as its high build allows it to fill minor cracks and defects. Dulux Acrylic Sealer Undercoat has excellent hiding power and sanding properties. It is a low VOC and low odour water based prepcoat. Dulux Acrylic Sealer Undercoat is highly recommended wherever a smooth finish is required.



Features and Benefits

- Ease of application
- Universal & multipurpose
- Dual purpose
- Excellent spreading, wet edge, quick to apply, quick drying
- Can be used under either oil based or water based topcoats
- Doubles as both a sealer and undercoat for most work
- Low odour

Standards And Certifications

Eco Choice Aotearoa
License No: 705019

Eco Choice Aotearoa Licensed Product

Standards and Certifications

For details on these standards and certifications please reference the 'Approvals' section at the beginning of this document.Please contact your DuluxGroup representative for specific information on ESD credits / points.

Uses

Dulux Acrylic Sealer Undercoat is suitable for sealing and undercoating Interior paper faced wallboards, render and hardboards. Suitable for use under both water or solvent borne topcoats. It is also designed for painting over roughly textured products such as Dulux Design™ Suede and Dulux Design Stone. Dulux Acrylic Sealer Undercoat is highly recommended wherever a smooth finish is required.

✓ **Interior** ✓ **Wall**

Precautions and Limitations

All preparation and painting must conform to AS2311: The Painting of Buildings.

Do not apply when the temperature is 10C or under or likely to fall below 10C during the drying period.

Tinter if added should be shaken and stirred in immediately and thoroughly.

Do not overspread, or exceed the recommended rate of 16 square metres per litre.

Performance Guide

Weather
Interior use only.

Heat Resistance **Resists temperatures up to 60 degrees.**	Water **Resists mild & intermittent exposure to steam & condensation as part of system.**
Solvent **Sensitive to aromatic hydrocarbons and alcohols.**	Abrasion **Not applicable**

Typical Properties

Gloss Level **Flat**	Thinner **Water**

Colour
White. May be tinted with DULUX Decorama Tinters up to 25 ml per litre.

Dulux Colour Base

✓ **White**

Components **1**	Number of Coats **1**
Toxicity **Lead free. Dry film is non-toxic and conforms to AS1647, Part 3.**	V.O.C. Level **<45g/L**

Meets ECNZ V.O.C. Requirements?
Yes

Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.

Touch Dry
20 Minutes

Clean Up

Water

Clean Up Description
Clean all equipment immediately with water.

Application Methods

Air Spray | Airless Spray | Brush | Roller

Application Conditions	Solids by Volume		
	35		
	Min	Max	Recommended
Wet Film Per Coat (microns)	63	63	63
Dry Film Per Coat (microns)	22	22	22
Recoat Time (min/hours)	2 Hours	Indefinite	
Theoretical Spread Rate (m²/L)	12	12	12

Application Guide

Surface Preparation

Previously painted surfaces: Thoroughly clean all surfaces free of loose dust, surface chalk, grease, mould, mildew, wax and loose or flaking paint. Wash with sugar soap. Treat mould contaminated areas with antimould. Rinse with clean water. Fill nail holes, imperfections and cracks with a suitable filler, sand and dust off. For use on paperfaced plasterboard and masonry. On bare set plaster, use 1 coat of DULUX Sealer Binder.

Application Procedure and Equipment

Brush, roller, conventional and airless spray.
Stir contents thoroughly before and during use with a broad, flat stirrer using an upward lifting action.

Brush/Roller: Pre-wet brushes and roller with water prior to use. A short or medium nap roller will give most uniform appearance. Apply a full even coat and finish by light parallel strokes with a practically dry roller.

Conventional/Airless Spray: Suitable for application by all standard spray equipment.

Health and Safety

SDS Number	SDS Link
DLX001420	View SDS Link

Please refer to SDS Link. In case of emergency, please call 0800 220 770.

Transport and Storage

Pack A

63052934

Size:	Weight:
1L 2L 4L 10L	1.655kg 3.235kg 6.390kg 15.609kg

Flash Point	UN Number
NA	NA
Dangerous Goods Class	**Package Group**
NA	NA

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.